













































































Standard Equipment

- Antifouling boat + drive (2x Prim. 3 Antif.)
- Batteries (4 deep discharge +1 start ~480Ah)
- Bowpropeller 6hp
- Canopy
- Charger and shoreconnection (35A-25m cable/)
- Curtains in cabins (non-blackout)
- Defroster 10 kW + Hot air outlets in cockpit
- El. main switches w/battery monitoring
- Electric bilge pump 2 pcs. (auto)
- Electric blackwater discharge from septic tank
- Electrical toilet with septic tank indicator
- Engine room lights
- Fire Alarm in cabins
- Freezer 28L /0,98 Cu Ft
- Fridge 130 L/ 4,5 Cu Ft
- Gas cooker
- Gas oven
- Hardtop
- Heater 5,5 kw
- Hydraulic steering
- Hotwater 220V-boiler (60L/15,8 gall)
- NMEA interface to navigation systems
- Shower on platform
- Stereo FM with external antenna and speakers, USB, Bluetooth, AUX (no CD player)
- Teak on saloon floor (no teak on aft deck flor, platform and dolboards)
- Teak over the rails and on fender box
- Interceptors (Trim tabs)
- Windscreen wipers with interval switch & washer from main water tank















MAREX 375

Technical Specifications

Hull type: Length:

Planing 12.05 m/39' 6" 3.55 m/11' 8"

Beam: Depth: Fuel tank:

1.05 m/3' 5" 700 Lt/ 184 gall

Water tank: 340 Lt/ 89 gall Hotwater: 60 Lt/15 gall Blackwater tank: 150 Lt/39 gall

CE Category:

Seats: 14 people

Bed forward cabin: 1.50 x 2.00 m/59 x 79 inches **Bed mid cabin:** 1.90 x 2.00 m/75 x 79 inches

Outside cockpit: Bathing platform: Batteries:

Berths:

Height without cradle including mast: Height above waterline without mast:

Weight empty boat: Width of side decks:

Design:

2.25 x 2. 60 m/7'4" x 8'5" 0.85 x 3.00 m/1'9" x 9'8" 4 + 1 = 480 AH 2 + 2 + 2

> 4.30 m/14' 11" 2.90 m/9' 5" 7,7 tonnes approx. 28 cm/0' 92"

Marex

